NR200 High Quality Colorimeter

- Humanity Design and Convenient Operation
- Stable Measurement Performance
- Convenient and Fast Locating
- PC Software—More Function Expansion
- Equipped with High Capacity Li-ion Battery











NR200 High Quality Colorimeter

1. Leading Humanity Design and Convenient Operation

- One-Touch Access to Measurement Interface
- Structure Design in line with Ergonomics
- Easy-to-use Operator Interface

2. Stable Measurement Performance

- The average fluctuation of ΔE is less than 0.08.
- Portable structure design is more conductive to keeping the instrument stable when using.

3. Flexible and Accurate Locating

• Illumination locating is a fast, simple and convenient locating which is created by 3nh.

4. PC Software—Realize More Function Expansion


- 3nh has the intellectual property of PC software. The corresponding software serial number and password protection are configured in 3nh colorimeter.
- Be able to perform color difference analysis, color difference cumulative analysis, chromaticity index, color sample database management, simulating object color, etc.

5. Advanced Power Management Design

- 3nh is the first enterprise using high capacity Li-ion battery in colorimeter.
- 3nh Li-ion battery can be repeatedly charged which will save cost. Meanwhile, it can measure more than 3000 times on one charge to ensure the stability of long time measurement.

E Total Color Aberration

- △L is large stands for the color is partial white.
- △L is small stands for the color is partial black. ∆a is large stands for the color is partial red.
- ∆a is small stands for the color is partial green.
- △b is large stands for the color is partial yellow.
- ∆b is small stands for the color is partial blue.



Applicable Industries



Technical Specifications

Illuminating/Viewing Geometry: 8/d Measuring Aperture: Φ8mm Detector: Silicon photoelectric diode

Color Space: CIEL*a*b*C*h* CIEL*a*b* CIEXYZ Color Difference Formula : △E*ab △L*a*b* △E*C*h*

Light Source: D65

Light Source Device: LED blue light excitation Errors Between Each Equipment : ≤0.50 ∆ E*ab Storage: 100pcs standards 20000pcs samples

Repeatability: Standard deviation within Δ E*ab 0.08 Average of 30 measurements of standard white plate

Weight: 500g

Dimension: $205 \times 70 \times 100 \text{ mm}$

Power source: Rechargeable lithium-ion battery 3.7V@3200mAh

Lamp Life: 5 years, more than 1.6 million measurements

APPLIED TESTING SYSTEMS PVT. LTD.

Address: A-63, Sector-58, Noida 201 301, Uttar Pradesh, India

Phone: +91 70425 20222, +91 98186 01238

Email: sales@atsin.in, saksham@atsin.in, website: www.atsin.in

